

T.T.D. Application Tape

SPECIFICATIONS

 Composition	 Average Thickness	 Carrier	 Available in 4 versions	 Certifications
adhesive PES	75-80* microns	Silicon paper	TTD Advanced (low tack) TTD Easy (medium tack) TTD Evolution (high tack) TTD Special (high tack)*	REACH compliant

TO BE USED WITH

Product	TTD Advanced (low tack)	TTD Easy (medium tack)	TTD Evolution (high tack)	TTD Special (high tack)
COLORPRINT®	OK	OK	OK	
COLORPRINT® EXTRA	OK	OK	OK	
COLORPRINT® NEW M		OK	OK	
COLORPRINT® PU		OK	OK	
COLORPRINT® PU EXTRA		OK	OK	
EASY SUBLI®				OK
HI-5 PRINT		OK	OK	
SOFT PRINT COLOR		OK		
SUBLITHIN MATT LT		OK	OK	
EASYCOLOR®DTV	OK			

 **NOTE:** We highly recommend to perform a test before launching a production

APPLICATION INSTRUCTIONS

- Remove the protective paper from T.T.D.
- Apply the T.T.D. onto the printed logo, manually or using a laminator, avoiding air bubbles
- Remove the backing of the digital, printed media
- Heat apply following the instructions of the digital media
- Remove T.T.D. according the given instructions for the product in use..

 This document can be subject to variations. Updated versions are available on www.siser.com
For further information, please contact our sales office: info@siser.it



Siser s.r.l.
Viale della Tecnica,
18 36100 Vicenza -
Italy

Tel. +39 0444.287960
Fax +39 0444.287959
info@siser.it
www.siser.com

r.e.a. vi 171856
reg. imp. vi n° 14971
c.s. € 103.300 i.v.
p.iva 01591490246



Management
System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID: 9105027958

